

Hisense

Equivalent
to Previous
25/30
PINTS

DEHUMIDIFIER EASY CONTROL
up to 700 sq ft coverage

MODEL **DH3020K1W**



- Full bucket indicator avoids overflows
- Simple manual operation, and unit will run continuously if you press the “Minus” button until “CO” flash for 5 seconds and then display
- Single fan speed
- Low-temperature operation (38°F)



Low Noise Airflow System

High performance centrifugal fan ensures quiet operation with just 45d8(A)



Energy Efficient

Energy Star means its more energy efficient and helps reduce your utility bill



Filter Indicator

Washable filter helps to reduce bacteria, odors, and particles



Warranty

Two (2) years Parts & Labor

Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH3020K1W Energy Star 25* Pint Single Speed Dehumidifier quietly collects water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Easy control and the very low sound level make this a versatile choice. Additional features include an adjustable humidistat, easy accessible and washable filter, and full-tank alert.

Note:

*: New DOE test procedure, equivalent to previous 100 Pints:

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA. All rights reserved

TECHNICAL SPECIFICATIONS

Performance

Model #	DH3020K1W
Dehumidification(Pints/24 hours)	25*
Heating Capacity	N/A
Coverage	Up to 700 sq ft
Refrigerant	R-410A
Noise Level in dB(A)	45 dB(A)

Electrical

Voltage / Freq / Amps	115V / 60Hz / 3.7A
-----------------------	--------------------

General Features

Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	N/A
Display Type	LED
Continuous Run	Yes
Auto Dry	N/A
Manual Setting	30% ~ 80%
Timer-Clock	N/A
Fan Speeds	Single Fan Speed
Pump Mode	No

Refrigeration Compartment

Auto Bucket Shutoff	Yes
Bucket Capacity	8.5 pints
Bucket Shutoff Capacity	7.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	N/A

Accessories

Quick Connect Hose	No
--------------------	----

Approvals

Safety	UL
Energy	Energy Star

Shipping

Unit Dimension WxDxH (mm)	334 x 218 x 505
Carton Dimension WxDxH (mm)	380 x 266 x 535
Net Weight /Gross Weight (kg)	12.8 / 14.0

Unit Dimension WxDxH (inch)	13.2 x 8.6 x 19.9
Carton Dimension WxDxH (inch)	15.0 x 10.5 x 21.1
Net Weight /Gross Weight (lbs)	28.2 / 30.8
Loading (40HQJ)	1358
Loading (53')	1248 (floor loaded)
Warranty/UPC	
Parts & Labor	2 Years
UPC	819130026824

Note:

*: New DOE test procedure, equivalent to previous 30 Pints:

Product Images

Control Panel



Gravity draining with garden hose (not included)



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA. All rights reserved



Hisense USA Corporation
7310 McGinnis Ferry Road Suwanee, GA 30024
1-877-465-3566
www.hisense-usa.com