

# Hisense

Equivalent to  
Previous  
**25/30**  
PINTS

DEHUMIDIFIER EASY CONTROL  
up to 1500 sq ft coverage

MODEL DH3020K1W



- Full bucket indicator avoids overflows
- Simple manual operation, and unit will run continuously if you press the “Minus” button until “CO” flash for 5 seconds and then display
- Single fan speed
- Low-temperature operation (38°F)



**Low Noise Airflow System**  
High performance centrifugal fan ensures quiet operation with just 45dB(A)



**Energy Efficient**  
Energy Star means its more energy efficient and helps reduce your utility bill



**Filter Indicator**  
Washable filter helps to reduce bacteria, odors, and particles



**Warranty**  
Two (2) years Parts & Labor

## Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH3020K1W Energy Star 25\* Pint Single Speed Dehumidifier quietly collects water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Easy control and the very low sound level make this a versatile choice. Additional features include an adjustable humidistat, easy accessible and washable filter, and full-tank alert.

Note:

\*: New DOE test procedure, equivalent to previous 30 Pints:

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA. All rights reserved

## TECHNICAL SPECIFICATIONS

### Performance

Model #	DH3020K1W
Dehumidification(Pints/24 hours)	25*
Heating Capacity	N/A
Coverage	Up to 1500 sq ft
Refrigerant	R-410A
Noise Level in dB(A)	45 dB(A)

### Electrical

Voltage / Freq / Amps	115V / 60Hz / 2.7A
-----------------------	--------------------

### General Features

Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	N/A
Display Type	LED
Continuous Run	Yes
Auto Dry	N/A
Manual Setting	30% ~ 80%
Timer-Clock	N/A
Fan Speeds	Single Fan Speed
Pump Mode	No

### Refrigeration Compartment

Auto Bucket Shutoff	Yes
Bucket Capacity	8.5 pints
Bucket Shutoff Capacity	7.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	N/A

### Accessories

Quick Connect Hose	No
--------------------	----

### Approvals

Safety	UL
Energy	Energy Star

### Shipping

Unit Dimension WxDxH (mm)	334 x 218 x 505
Carton Dimension WxDxH (mm)	380 x 266 x 535
Net Weight /Gross Weight (kg)	12.8 / 14.0

Unit Dimension WxDxH (inch)	13.2 x 8.6 x 19.9
Carton Dimension WxDxH (inch)	15.0 x 10.5 x 21.1
Net Weight /Gross Weigh t (lbs)	28.2 / 30.8
Loading (40HQJ)	1358
Loading (53')	1248 (floor loaded)
<b>Warranty/UPC</b>	
Parts & Labor	2 Years
UPC	819130026824

Note:

\*: New DOE test procedure, equivalent to previous 30 Pints:

## Product Images

Control Panel



Gravity draining with garden hose (not included)



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2019 Hisense USA. All rights reserved



Hisense USA Corporation  
7310 McGinnis Ferry Road Suwanee, GA 30024  
1-877-465-3566

[www.hisense-usa.com](http://www.hisense-usa.com)