Dishwasher

Model HUI6220XCUS

Hisense



- Auto dry automatically opens the door slightly at the end of every cycle allowing excess steam to escape, ensuring washed items including plastics placed on top or bottom rack, dry completely
- Fingerprint resistant stainless steel exterior door allows for easy cleaning without using harsh chemicals and keeps your dishwasher looking great
- Automatic program always clean dishes, regardless of the load, thanks to the sensor technology, the automatic programming makes it possible to automatically adjust the program to the amount of the dishes loaded and the level of their dirtiness
- 3 Prong power cord is included for installation, junction box for hard wire application is sold separately

Even with a full house you can clean all your dishes at once in this Hisense dishwasher. This model features 5 different cycles – from heavy to to normal and offers a boost option. This dishwasher operates very quietly and provides a sound signal to notify you once the cycle is complete. The automatic door open function opens at the end of the cycle allowing steam to escape and results in completely dried dishes, even the plastic ware. The stainless-steel door with anti-finger coating means easy clean up and a beautiful appearance in your kitchen. The self-cleaning function will keep the interior pristine.

Hisense

Dishwasher

Model HUI6220XCUS

TECHNICAL SPECIFICATIONS

Efficiency	
Model#	HUI6220XCUS
Wash performance	A
Dry performance	A
Noise level	47 dB(A)re 1 pW
Max. temperature of inflow water	0° C
Motor	Asynchronous single phase motor
Control	
Control	Touch Control
Program	
Number of program	5
Main washing temperature(s)	70, 65, 55, 45, 35 °C
Personalization of program	Memory program
Safety	
Anti flood protection	Anti Flood System
Tub material	Stainless steel tub
Technical data	
Water connection	Cold+Hot-1-2
Height	857 mm
Depth (incl. wall spacing)	61 cm
Product dimensions (HxWxD)	85,7 × 60,5 × 57,8 cm
Dimensions of packed product (HxWxD)	93 × 64 × 66,5 cm
Weight (gross/net)	32 / 29,1 kg
Consumption data (IEC standard EN 50242)	
Water consumption	13,2
Energy consumption - label program	1,2 kWh
Noise level	47 dB(A)re 1 pW
Design	
Control panel type	Plastic
Control panel color	Black
Control panel inlay	Black PC
Buttons color	Black/Touch
Door type	Full stainless steel
Door sliding system	No
Door frame	Yes - handle pocket
Plinth color	Silver
L	I

Product Image





All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA. All rights reserved.

Hisense USACorporation 7310 McGinnis Ferry Road. Suwanee. GA. 30024 1-877-465-3566

www.hisense-usa.com