



- Bucket full indicator prevents overflows
- 3 Modes – Auto, Continuous, Manual
- 3 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38°F)



### Low Noise Airflow System

High-performance centrifugal fan ensures quiet operation at 46 dB(A) with the fan set on “Low”.



### Energy Efficient

Energy Star means it's more energy efficient and helps reduce your utility bill.



### Filter Indicator

Washable filter helps to reduce bacteria, odors and particles.



### Warranty

2 Years Parts & Labor.

## Control Humidity – Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH7021K1W Energy Star 50 Pint 3-Speeds Dehumidifier quietly collects water into the slide-out internal bucket or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly, this dehumidifier can operate at temperatures as low as 38°F. Three operating modes (manual, continuous, and auto dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

## TECHNICAL SPECIFICATIONS

Model #	DH7021K1W
<b>Performance</b>	<b>Performance</b>
Dehumidification (Pints/24 hours)	50
Coverage	Up to 4500 sq ft
Refrigerant	R-410A
Noise Level in dB(A)	46-48 dB(A)
<b>General Features</b>	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	Dimmable LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer	Yes, 30 minutes to 24 hours
Fan Speeds	3 Speeds (HIGH AUTO LOW)
Auto Bucket Shutoff	Yes
Garden Hose Connection	Yes, garden hose not included
Washable Filter	Yes

<b>Electrical</b>	
Voltage / Freq / Amps	115V / 60Hz, 7.0A* / 4.9A
Power Cord Length	6 feet
<b>Approvals</b>	
Safety	UL
Energy	Energy Star
<b>Shipping</b>	
Unit Dimension WxHxD (mm)	384 x 629 x 272
Net Weight (kg)	17.9
Unit Dimension WxHxD (inch)	15.1 x 24.8 x 10.7
Net Weight (lbs)	39.5
<b>Warranty/UPC</b>	
Parts & Labor	2 Years
UPC	819130027272

Note:

\*: Rated Amps(A) / accorded UL 60335 Safety

## Product Images

### Control Panel




### 2 Draining Options

Bucket conveniently located on front with handle for easy emptying



Use a garden hose (not included) for continuous draining to avoid emptying the bucket.



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-888-935-8880  
www.hisense-usa.com