



Google and Android are trademarks of Google LLC.



Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates



Google and Android are trademarks of Google LLC.



Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates



- Bucket full indicator avoids overflows
- 3 Modes – Auto, Continuous, Manual
- 3 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38°F)



### ConnectLife Control

Free ConnectLife APP for both iOS and Android™ allows you to control your dehumidifier with a smartphone from any location.



### Low Noise Airflow System

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on “Low”.



### Energy Efficient

Energy Star means it's more energy efficient and helps reduce your utility bill.



### Filter Indicator

Washable filter helps to reduce bacteria, odors and particles.



### Warranty

2 Years Parts & Labor.

## ConnectLife Dehumidifier – Monitor your dehumidifier and control humidity levels from your smart phone

The Hisense DH7021W1WG ConnectLife smart control 50 Pint 3-Speeds Dehumidifier conveniently controls humidity in your home from anywhere you are. With cloud-based connectivity via your iOS or Android smartphone, and the free ConnectLife App, you'll always be able to keep tabs on things at home. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Three operating modes (manual set, continuous and auto-dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

## TECHNICAL SPECIFICATIONS

|                                   |                               |
|-----------------------------------|-------------------------------|
| Model #                           | DH7021W1WG                    |
| <b>Performance</b>                | <b>Performance</b>            |
| Dehumidification (Pints/24 hours) | 50                            |
| Coverage                          | Up to 4500 sq ft              |
| Refrigerant                       | R-410A                        |
| Noise Level in dB(A)              | 46-48 dB(A)                   |
| <b>General Features</b>           |                               |
| Unit Control Type                 | Electronic                    |
| Fan Control                       | Button                        |
| Adj. Humidity Control             | Yes                           |
| Display Type                      | Dimmable LED                  |
| Continuous Run                    | Yes                           |
| Auto Dry                          | Yes                           |
| Manual Setting                    | 30% - 80%                     |
| Timer                             | Yes, 30 minutes to 24 hours   |
| Fan Speeds                        | 3 Speeds (HIGH AUTO LOW)      |
| Auto Bucket Shutoff               | Yes                           |
| Garden Hose Connection            | Yes, garden hose not included |
| Washable Filter                   | Yes                           |

|                             |                                |
|-----------------------------|--------------------------------|
| <b>Electrical</b>           |                                |
| Voltage / Freq / Amps       | 115V / 60Hz, 7.0A* / 4.9A      |
| Power Cord Length           | 6 feet                         |
| <b>Smart Technology</b>     |                                |
| Amazon and Google Enabled   | ConnectLife App (Android, iOS) |
| <b>Approvals</b>            |                                |
| Safety                      | UL                             |
| Energy                      | Energy Star                    |
| <b>Shipping</b>             |                                |
| Unit Dimension WxHxD (mm)   | 384 x 629 x 272                |
| Net Weight (kg)             | 17.9                           |
| Unit Dimension WxHxD (inch) | 15.1 x 24.8 x 10.7             |
| Net Weight (lbs)            | 39.5                           |
| <b>Warranty/UPC</b>         |                                |
| Parts & Labor               | 2 Years                        |
| UPC                         | 819130027296                   |

Note:

\*: Rated Amps(A) / accorded UL 60335 Safety

## Product Images

### Control Panel




### 2 Draining Options

Bucket conveniently located on front with handle for easy emptying



Use a garden hose (not included) for continuous draining to avoid emptying the bucket.



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-888-935-8880  
www.hisense-usa.com