

# Hisense

550  
SQ.FT

PORTABLE AIR CONDITIONER  
SACC 12,000BTU

Model AP1221CR1W



- Powerful cooling capacity
- Fast install with window kit and pre-installed vent hose
- Cool, Dehumidify, and Fan Functions
- Remote Control is Included
- 2-year Warranty



### Simple Installation

Easy-to-install window kit with pre-installed vent hose



### Quiet Operation



### Drain-free Operation (Cooling mode)



### Snap-assembly Window Kit

## Powerful, Quiet, and Quick Installation

The Hisense AP1221CR1W Portable Air Conditioner delivers maximum performance and convenience. New design provides long-distance airflow that is cool and quiet. Additionally, the air vent louver automatically opens to a preset position after the unit is powered on. Use included remote to adjust the automatic air vent louver. Quick installation using easy-to-install snap-together Window Kit and pre-installed vent hose. Window kit is for a window 18" – 50" wide.

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2019 Hisense USA. All rights reserved  
\*: Smartphone not included. App requires either iOS 11 or higher or Android 6 or higher. Home wifi router required for pairing between product and smartphone.

|  |                               |
|--|-------------------------------|
| <b>Model #</b>                                     | <b>AP1221CR1W</b>             |
| <b>Performance</b>                                 |                               |
| Maximum Cooling space                              | 550 sq. ft.                   |
| Cooling Capacity - SACC (BTU)                      | 12,000                        |
| CEER   | 8.4                           |
| Dehumidification Pint / 24 hr (at 26.7° / 19.4° C) | 100.8                         |
| Refrigerant  | R-32                          |
| Airflow (CFM)                                      | 175 – 230                     |
| Noise Level in dB(A)                               | 51 - 55                       |
| <b>Electrical</b>                                  |                               |
| Voltage / Freq / Amps                              | 115V / 60Hz, 12A* / 11A       |
| Plug Type / NEMA#                                  | A / 5-15P                     |
| Power Cord Length (feet)                           | 4.9                           |
| <b>Control Features</b>                            |                               |
| Unit Control Type                                  | Electronic                    |
| Fan Control  | Button                        |
| Thermostat Control                                 | 61 - 86 °F                    |
| Display Type                                       | Dimmable LED                  |
| Sleep Mode   | Yes (on remote)               |
| Dehumidifier Mode                                  | Yes                           |
| Cooling Speeds                                     | 3 Speeds                      |
| Temp Display Units                                 | c / °F                        |
| Timer  | 1 Hr - 24Hr On/Off            |
| Auto Restart                                       | Yes (after power is restored) |
| <b>General Features</b>                            |                               |
| Removable Filter                                   | Yes                           |
| Washable PP Filter                                 | Yes                           |
| Oscillating Air Vent Louvers                       | Yes (on remote)               |
| Vent System  | Single Hose. 5.9"0 x 59"L     |
| <b>Accessories</b>                                 |                               |
| Remote Control                                     | Yes                           |
| AAA Batteries                                      | Yes                           |
| Air Hose   | Yes                           |
| Window Kit   | Yes                           |
| <b>Approvals</b>                                   |                               |
| Safety   | ETL                           |
| Energy Star  | No                            |

|                               |                    |
|-------------------------------|--------------------|
| <b>Product Dimensions</b>     |                    |
| Unit Dimension W x H x D (mm) | 460 x 842 x 415    |
| Net Weight (Kg)               | 38                 |
| Unit Dimension WxHxD (inch)   | 18.1 x 33.1 x 16.3 |
| Net Weight (lbs)              | 83.8               |
| <b>Product</b>                |                    |
| Parts & Labor                 | 2 years            |
| UPC                           | 819130027432       |

Note:

\*: Rated Amps(A) / accorded UL 60335 Safety

### Easy installation



1  
Install window kit



2  
Extend the pre-installed hose and snap into window kit



3  
Plug in.




4  
Turn on and enjoy!

### Control Panel



### Window Size



The window installation kit allows you to install the air conditioner in most vertical-sliding windows 18" to 50" wide, or horizontal-sliding windows from 18" to 50" high.



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2021 Hisense USA. All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-877-465-3566  
[www.hisense-usa.com](http://www.hisense-usa.com)