Hisense



WINDOW AIR CONDITIONER

With Inverter Technology & ConnectLife App

Model AW1022TW1W 450 Sq. Ft.



- Inverter technology ensures energy efficiency and ultra-quiet operation: 37 dBA
- 3 modes (Cooling, Fan, Dehumidifier) for versatile comfort
- ConnectLife smart app allows easy control from anywhere
- · Remote control for easy, convenient operation
- · 2-year warranty provides peace of mind
- Washable, removable filter for quick, easy cleaning
- 4-way air direction provides even, consistent comfort
- Meets ENERGY STAR® standards, saving on energy costs





Excellent Energy Efficiency



Ultra-Quiet Operation



ConnectLife Smart App



115 Volt / 15 Amps









The Hisense AW1022TW1W Window Air Conditioner with Heat is best suited for smaller rooms (450 sq. ft. or less), delivering 10,000 BTU of cooling power. It provides three modes of comfort – cooling, fan, or dehumidifier – allowing you to choose the comfort you want at any time. The washable air filter is easy to remove and easy to clean, keeping it fresh and free from unwanted odors and bacteria. Its energy-efficient design meets ENERGY STAR® requirements, and inverter technology ensures ultra-quiet operation for a peaceful night's sleep. Includes a remote control that puts easy operation right at your fingertips. Backed by a 2-year warranty on both parts and labor.

Hisense

450 sq. ft

Window Air Conditioner
10,000 BTU
Model AW1022TW1W

Model #	AW1022TW1W
perfomence	•
Cooling Capacity -(BTUs/hr)	10000
CEER	15
Coverage	450 sq ft
Dehumidification Pint / 24 hr	26.4
Refrigerant	R-32 /320g
Airflow (CFM)(High/LOW)	178-262
NOise Level in dB(A)	53
Electrical	•
Voltage / Freq / Amps	115 - 60/9.7,11.2
Plug Type / NEMA#	A / 5-15P
Watts-cooling	900
Electrical Receptacle	115V/15A
Power Cord Length (feet)	6'(1.8m)
Control Features	
Thermostat Type	Electronic
Fan Speeds - Cool/Fan	3/3
Display Type	LED
Timer	YES
Unit Features	
Chassis Type	Fixed
Air Deflection	4-Way
Air Discharge Type	Тор
Washable Filter	YES, Easy Access
Accessories	•
Installation Kit	YES
Remote Control	10
Approvals	
Safety	cULus
Energy Star	YES

Product Dimensions		
Unit Dimension W x H x D (mm)	480 × 370 × 545	
Net Weight (kg)(fits NOt included)	23.5	
Unit Dimension WxHxD (inch)	18.90 × 14.577 × 21.46	
Net Weight (lbS)(fits NOt included)	51.8	
Product		
Parts & Labor	Two years	
819130029870	819130029870	

NOte:


*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Sleek Design with Touch Control



Window Opening



A: 13 3/5" (34.5cm) min B: 24 1/2" (62.2cm) - 39" (99.1cm)



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2021 Hisense USA, All rights reserved

Hisense USA Corporation 7310 McGinnis Ferry Road, Suwanee, GA,30024 1-888-935-8880 www.hisense-usa.com