

Hisense

35
PINT

DEHUMIDIFIER AUTO-DRY

up to 700 sq.ft. coverage

Model: DH35K1W



- Bucket full indicator avoids overflows
- 3 Modes - Auto, Continuous, Manual
- 2 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38 deg F)



Low noise airflow system

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on "Low".



Energy Efficient

Energy Star means its more energy efficient and helps reduce your utility bill.



Filter Indicator

Washable filter helps to reduce bacteria, odors and particles



Warranty

2 Years Parts & Labor


Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense DH35K1W Energy Star 35-Pint 2-Speed Dehumidifier quietly collects water into the slide-out internal bucket, or can discharge the water via connecting a garden hose (not included) through the side of the cabinet. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38 degrees Fahrenheit. Three operating modes (manual set, continuous and auto dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.


TECHNICAL SPECIFICATIONS

Performance	
Hisense-Model	DH35K1W
Dehumidification (Pints/24 hrs)	35 (DOE Test Procedure)
Heating Capacity	N/A
Coverage	Up to 700 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	46 - 48 dB(A)
Electrical	
Voltage / Freq / Amps	115V/60Hz / 3.7 A
Control Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer-Clock	Yes
Fan Speeds	2 speeds (Lo, Hi, Auto)
Pump Mode	No
General Features	
Auto Bucket Shutoff	Yes
Bucket Capacity	11.4 pints
Bucket Shutoff Capacity	8.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	N/A
Accessories	
Quick Connect Hose	No
Approvals	
Safety	UL
Energy	Energy Star / CEC
Parcel Shippable	Yes
Shipping	
Unit Dimension WxDxH (mm)	356 X 273 X 507
Carton Dimension WxDxH (mm)	405 X 335 X 535
Net Weight /Gross Weight (Kg)	14.4/16.0
Unit Dimension WxDxH (inch)	14.0 X 10.8 X 20.0
Carton Dimension WxDxH (inch)	16.0 X 13.3 X 21.0
Net Weight /Gross Weight (lbs)	31.7/35.2
Loading(40HQ)	1020

Loading (53')	936 (floor loaded)
Warranty/UPC	
Parts & Labor	2 years
UPC	857603006331



Control Panel



Gravity Draining with Garden Hose (not included)

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2017 Hisense USA. All rights reserved

Hisense USA Corporation
7310 McGinnis Ferry Road, Suwanee, GA, 30024
1-877-465-3566
www.hisense-usa.com

