

**Model: DH70KP1WG**



- Built-in Pump, quick-connect hose included
- 3 Modes - Auto, Continuous, Manual
- 2 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38 deg F)



**Low noise airflow system**

High-performance centrifugal fan ensures quiet operation, achieving just 46 dB(A) with the fan set on "Low".



**Energy Efficient**

Energy Star means its more energy efficient and helps reduce your utility bill.



**Filter Indicator**

Washable filter helps to reduce bacteria, odors and particles



**Warranty**

2 Years Parts & Labor

**Built-in Pump - Helps keep your home conveniently dry, fresh, and quiet**

The Hisense DH70KP1WG Energy Star 70-Pint 2-Speed Dehumidifier has a built-in pump that can quietly discharge water out a basement window or into a sink using the included quick-connect hose. This is a reliable and eco-friendly dehumidifier which can operate at temperatures as low as 38 degrees Fahrenheit. Three operating modes (manual set, continuous and auto dry) and the very low sound level make this a versatile choice. During dehumidification, water accumulates in the internal water tank or is continuously pumped out using the included quick-connect. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

## TECHNICAL SPECIFICATIONS

Performance	
Hisense-Model	DH70KPIWG
Dehumidification (Pints/24 hrs)	70 (DOE Test Procedure)
Heating Capacity	N/A
Coverage	up to 1,000 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	46 - 48 dB(A)
Electrical	
Voltage / Freq / Amps	115V/60Hz / 6.8 A
Control Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer-Clock	Yes
Fan Speeds	2 speeds (Lo, Hi, Auto)
Pump Mode	Yes
General Features	
Auto Bucket Shutoff	Yes
Bucket Capacity	13.7 pints
Bucket Shutoff Capacity	11.0 pints
Garden Hose Connection	Yes - garden hose not included
Washable Filters	Yes
Max Pump Discharge Height	16 feet (head)
Accessories	
Quick Connect Hose	Yes, included (9mm dia)
Approvals	
Safety	UL
Energy	Energy Star / CEC
Parcel Shippable	Yes
Shipping	
Unit Dimension WxDxH (mm)	387 X 300 X 628
Carton Dimension WxDxH (mm)	435 X 335 X 667
Net Weight /Gross Weight (Kg)	21.3/23.0
Unit Dimension WxDxH (inch)	15.3 X 11.8 X 24.7
Carton Dimension WxDxH (inch)	17.1 X 13.3 X 26.3
Net Weight /Gross Weight (lbs)	46.8/50.7
Loading(40HQ)	746

Loading (53')	624 (floor loaded)
Warranty/UPC	
Parts & Labor	2 years
UPC	857603006294



Control Panel



Quick Connect Hose

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2017 Hisense USA. All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-877-465-3566  
www.hisense-usa.com

